



| Type | b mm | a mm | h ₁ mm | h ₂ mm | Capacity Grain dm ³ | Capacity max. Water dm ³ | Number buckets per 1 m | Standard Punching moulded recessed holes | | | |
|---------------|---------|---------|----------------------|----------------------|--------------------------------------|---|------------------------------|---|---------|---------|-----|
| | | | | | | | | d mm | e mm | f mm | No. |
| H 100-090 HDP | 107 | 91 | 62 | 37 | 0,29 | 0,19 | 15 | 8,5 | 50 | 17 | 2 |
| H 130-120 HDP | 140 | 115 | 80 | 55 | 0,63 | 0,41 | 11 | 8,5 | 70 | 23 | 2H |
| 180-140 HDP | 188 | 144 | 92 | 60 | 1,20 | 0,90 | 10 | 8,5 | 100 | 30 | 2 |
| H 230-170 HDP | 240 | 172 | 110 | 73 | 2,40 | 1,65 | 9 | 10,5 | 120 | 38 | 2 |
| H 280-170 HDP | 290 | 174 | 110 | 70 | 2,89 | 2,08 | 9 | 10,5 | 2x80 | 36 | 3H |
| 300-180 HDP | 310 | 190 | 110 | 74 | 3,90 | 2,46 | 9 | 9,0 | 2x100 | 35 | 3H |
| 330-215 HDP | 340 | 220 | 138 | 94 | 5,40 | 3,92 | 6,5 | 10,5 | 2x120 | 38 | 3H |
| 350-180 HDP | 370 | 190 | 115 | 78 | 4,51 | 3,30 | 7,5 | 9,0 | 3x90 | 35 | 4H |
| 370-215 HDP | 380 | 220 | 142 | 94 | 6,30 | 4,41 | 6 | 10,5 | 3x90 | 36 | 4 |

- ▶ **for conveying of:** all kinds of bulk material
- ▶ **for use at:** Silos, mills, feed mills, malt- sugar- and foods industry, chemical industry
- ▶ **Material:** HDPE (High Density Polyethylene)
work temperature: - 50 °C up to + 80 °C
Nylon 6 (Polyamid 6)
work temperature: -30 °C up to + 100 °C, short time 140 °C
- ▶ **Feature:** high wear-resistance, extensibility at break 300 %
- ▶ **Punching:** Special punching available on request
the buckets have a flat back wall

All statements are not binding, technical alterations subject to change

High duty buckets of HDPE
shallow rounded design

