



b mm	a mm	h ₁ mm	h ₂ mm	r ₁ mm	r ₂ mm	Capa- max.		Standard punching			Weight		Sheet-		
						city	number	d	e	f	kg/1000pc	s ₁	s ₂		
						dm ³	per 1 m	mm	mm	mm	No.	green	white	mm	mm
80	80	78	42	190	19	0,11	10	8	45		2	35		2	2
100	95	93	50	225	23	0,25	8,5	8	48		2	60	50	2	2
120	105	105	50	260	26	0,45	8	8	63		2	90	72	2,5	2,5
140	115	110	60	290	29	0,60	6,5	8	80		2	120	95	2,5	2,5
160	130	120	75	315	32	0,90	5,5	8	96		2	185	130	3	
	3180	130	135	75	335	34	1,10	5,5	8		103	2	205	160	3
	3200	140	150	75	355	36	1,35	5	10		118	2	290	230	3
	4250	170	165	80	400	40	2,00	5	10		2x77	3	480	360	3,5
	4315	185	170	105	450	45	3,00	4,5	11		2x109	109	3809	620	4,5

5

Special punching not available

- ▶ **for conveying of:** light, granulated goods, sticking and adhesive products
- ▶ **for use at:** Mills, feed mills, malt-, sugar- and foods industry
chemical industry
- ▶ **Material:** Polyethylene (white), work-temperature up to 60 °C
Polyamid (grey/green), work-temperature up to 110 °C

Plastic buckets
shallow, rounded buckets similar DIN 15232

